



# DEMO Bulletin

Oct. 29, 2012



HOSS 700 Rotary Cleaning Tool

PRIOR to doing a demo READ  
Page 2 & 7 of Owner's Manual

"Changing the Orifices"

Review the Owners Manual that covers changing the orifices.

Look at Page (2) Figure (1) and letter "H" is the filter housing on the handle that you take apart to change the orifice, the stainless steel filter is in the same housing, and the customers should be informed of that fact as it eventually needs to be cleaned out. I suggest installing the smallest one (.048) they are numbered with the lower numbers being the smallest opening which restrict more water than the larger number obviously.

Here is what the manual says on page 7.

**Adjust solution flow.** The flow of solution can be customized to soiling conditions and type of cleaning equipment used. To provide maximum solution flow, the HOSS is shipped without a restrictor installed. **The Hoss 700 is supplied with .048, .052, and .057 in.** flow-restricting orifices. Customers who wish to restrict flow may add one of the restrictors provided to the inline filter assembly **(Fig. 1, H)**. To install a restrictor, disassemble the in-line filter, place the restrictor in position between the filter screen and the nut, and reassemble. For best results, always groom the carpet after cleaning. Always establish adequate drying conditions after cleaning.

Please let me know if I can be of further assistance.

Cheers,  
Bryan Thomson / I.C.E.  
Hard Surface Specialist  
Sapphire Scientific  
360-420-7274